



PROSCAF

SMARTROOF

by



SAFESMART
ACCESS



Reaching new heights

02 8844 4500 www.proscaf.com

The Proscaf SmartRoof is a temporary roof system designed as an extension of the Proscaf range from SafeSmart Access. Based on feedback from the scaffolding and construction industries, the Proscaf SmartRoof has been design and engineered to allow scaffold contractors to provide their construction clients with better solutions onsite helping drive efficiency and safety.

Proscaf SmartRoof joins the other auxiliary Proscaf products including the Proscaf SwiftStage, ProPanel and SmartBridge to provide a complete range of temporary works solutions for the construction industry.

Designed to reduce waste onsite, help projects finish ahead of schedule, and maximise the utilisation of equipment – Proscaf SmartRoof has been tested under the harshest conditions onsite and in digital simulations to ensure the system lasts the test of time.



Unique sliding coupler allows Proscaf SmartRoof rail to be mounted to any truss configuration



5-45 degree adjustable mounts

Designed and engineered by SafeSmart Access, The Proscaf SmartRoof temporary roof system has been developed over 5 years to create a versatile, easy to use solution.

Some of the characteristics are:

Weather Protection: Using a high strength Ripstop polyester decitex canopy or 2.57M bays at lengths up to 20M (tear strength 400N WARP/300N WEFT), the Proscaf SmartRoof is designed to handle the challenges of any project and keep the weather off the project. Optional translucent Suntex polyester 833 decitex anti wicking canopy available.



Ease of Installation: The Keder track system means the installation can be carried out on a laydown site and craned into place. The polyester canopy slides up and over using the Proscaf SmartRoof roller, reducing time spent at height during installation.



Light weight: The aluminium truss and bracing system increases the speed of install over traditional roof bracing methods. The modular quick lock aluminium braces provide a light weight simple construction process. Unique truss beam adjustable mounts suit roof pitches of 5 – 45 degrees.

















Reusable: The canvas system allows the contractor to reuse the Proscaf SmartRoof on multiple projects. The reduction of plastic waste on construction sites is an environmental and cost advantage.




Engineered: The Proscaf SmartRoof comes with a pre-engineered data package for the Australian & New Zealand weather conditions to allow contractors to have their projects engineered for their sites faster and more economically.




STOCK NUMBER	DESCRIPTION	IMAGE
THJ1.2	Truss Beam Hip Joiner 20°	
SRHR20	SmartRoof Hip Rail 20°	
TB300 TB300-750 TB400 TB400 - 750 TB500 TB500-750 TB600 TB600-750	Truss Beam 3m x 530mm Truss Beam 3m x 750mm Truss Beam 4m x 530mm Truss Beam 4m x 750mm Truss Beam 5m x 530mm Truss Beam 5m x 750mm Truss Beam 6m x 530mm Truss Beam 6m x 750mm	
SRBF257	SmartRoof Brace Frame 2.57m x 1.0m	
SRL257	SmartRoof Ledger 2.57m	
SRD257 - 530 SRD257 - 750	SmartRoof Diagonal Brace 2.57m x 530mm SmartRoof Diagonal Brace 2.57m x 750mm	
SRST257-530 SRST257-750	SmartRoof Sectional Truss 2.57m x 530mm SmartRoof Sectional Truss 2.57m x 750mm	
SREB530 SREB750	SmartRoof Eave Bracket 530mm SmartRoof Eave Bracket 750mm	
SRAM	SmartRoof Adjustable Mount 0.73m/1.09m	
SRS257	SmartRoof Sheeting Available per metre	
SRR	SmartRoof Rail Extrusion available per metre	
SRC	SmartRoof Half Coupler	
SRS	SmartRoof Spigot	
SRW	SmartRoof Wedge Head	

The 530 Truss beam system can span up to 15m at 120km wind speed before the high wind warning plan needs to be carried out. The 750 Truss beam system can span up to 20m at 120km wind speed before the high wind warning plan needs to be carried out. Diagonal brace only to be used on 750 Truss Beam System.













PROSCAF

SMARTROOF

www.proscaf.com

SYD 02 8844 4500 - MEL 03 9309 0544 - BNE 07 3266 7111

